

30. (New) A system for sleep surface adjustment, wherein said sleep surface is provided by a sleep support system that is configured for at least two users, wherein said sleep surface is supported by at least two fluid chambers whose pressure is independently adjustable, and wherein said two fluid chambers are surrounded by an upper wall, lower wall, and a pair of side walls each having an interior and an exterior, said system comprising:

a topper pad, said topper pad positioned above said fluid chambers and extending from said exterior of one of said pair of side walls to said exterior of the other of said pair of side walls; and

a base pad, comprising an additional fluid chamber, wherein said base pad is positioned below at least one of said fluid chambers and is used to lift said fluid chamber to a desired height if necessary to reach said desired height.

31. (New) The system of claim 30, wherein said additional fluid chamber has an independently adjustable fluid pressure setting.

32. (New) The system of claim 30, wherein said additional fluid chamber is unitary with said fluid chamber.

33. (New) The system of claim 32, wherein said fluid chamber and said additional fluid chamber exchange fluid to maintain said fluid chamber at a desired height.

34. (New) A method for adjusting a sleep surface, wherein said sleep surface is provided by a sleep support system that is configured for at least two users, wherein said sleep surface is supported by at least two fluid chambers whose pressure is independently adjustable, and wherein said two fluid chambers are surrounded by an upper wall, lower wall, and a pair of side walls each having an interior and exterior, said method comprising the steps of :

determining a desired height for said fluid chambers within said sleep support system;
positioning a base pad, comprising an additional fluid member beneath at least one of said fluid chambers;

lifting said fluid chamber with said base pad if necessary to achieve said desired height;
and

placing a topper pad atop said fluid chambers, wherein said topper pad extends from said exterior of one of said pair of side walls to said exterior of the other of said pair of side walls.

35. (New) The method of claim 34, wherein said additional fluid chamber has an independently adjustable fluid pressure setting.

36. (New) The method of claim 35, wherein said fluid chamber and said additional fluid chamber exchange fluid to maintain said fluid chamber at said desired height.--

A large, stylized handwritten signature, possibly reading 'A', is located in the bottom right corner of the page.